

## 10 power cords C20 -C19 with locking

Catalogue number(s) : 6 442 01/02/03/  
 07/08/09/13/14/15



### 1. USE

Second generation S-Lock security system  
 Unique rotary switch and low profile C19 locking mechanism fits any standard C20 inlet  
 Rated up to 16 amps  
 Various colors and lengths

### 2. COMMON APPLICATIONS

Data centers  
 Medical devices  
 Automation industrial  
 Industrial equipment  
 Architectural devices  
 Broadcasting stations  
 Critical power management

### 3. DESCRIPTION

Cat number	Color	Length (m)
6 442 01	Black	1
6 442 02	Black	1.5
6 442 03	Black	2
6 442 07	Red	1
6 442 08	Red	1.5
6 442 09	Red	2
6 442 13	Blue	1
6 442 14	Blue	1.5
6 442 15	Blue	2

### 4. TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Rating	TUV : 16A 250VAC
Operation temperature	-20°C - +70°C
Flammability corresponding to	Cable (H05VVVF) : IEC60332-1. Cat F2
Conductor size	1.5mm <sup>2</sup>
Connector types	C20 - C19
Locking side	Server

### 5. STANDARDS AND APPROVALS



